6. What are the dimensions of a standard slab?

- Standard slabs measure 30″ x 96″ x 1.5″ thick

7. Are fibers used to enhance the structural integrity of Meld products?

- Yes. Unlike competitive concrete surfacing materials Meld slabs and products utilize a special fiber reinforcing component that increases the physical properties and structural integrity of the material as well as minimizes the shrinkage cracking associated with concrete products.

8. How many standard colors are there?

- A total of six (6) standard colors are available in each material.

9. Are slabs available in custom sizes and colors?

- Yes, Meld can provide custom slabs up to 60″ x 108″ x 1.5″ in size.
- Meld offers custom color matching capabilities, which make it possible to create virtually any color.

10. Can slabs be shipped to any location?

- Yes. Shipping is available anywhere.

11. How are slabs shipped?

- Slabs are packaged on edge on heavy duty pallets and shipped LTL Ground Freight. A maximum of six standard slabs are included on each slab pallet.

12. How are slabs fabricated and installed?

- Meld slabs are fabricated by local countertop fabrication shops and installed similarly to natural stone and quartz materials. Please refer to Meld's fabrication manual for up to date fabrication and installation guidelines.

13. Do the slabs have to be sealed?

- Yes. Meld slabs should be sealed using a sealer that is best suited for the application at hand. Please refer to Meld's fabrication manual for up to date sealer recommendations and sealing guidelines.